## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Burcau





(43) International Publication Date 22 January 2004 (22.01.2004)

PCT

(10) International Publication Number WO 2004/007782 A1

(51) International Patent Classification7: C22C 5/00, 5/04

(21) International Application Number:

PCT/GB2003/003037

(22) International Filing Date:

11 July 2003 (11.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0216323.6

13 July 2002 (13.07.2002) GB

(71) Applicant (for all designated States except US): JOHN-SON MATTHEY PUBLIC LIMITED COMPANY [GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): COUPLAND,

**Duncan, Roy** [GB/GB]; 68 Warren Wood Drive, High Wycombe HP11 1EA (GB). **HYDE, Robin** [GB/GB]; 5 Wilbury Close, Letchworth SG6 4JX (GB).

(74) Agent: WISHART, Ian, Carmichael; Johnson Matthey Technology Centre, Blounts Court, Sonning Common, Reading RG4 9NH (GB).

(81) Designated States (national): JP, KR, US.


(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## (54) Title: ALLOY



(57) Abstract: An iridium alloy consists essentially of iridium and at least one of W and Zr, and optionally Rh. When present, W comprises between 0.01 and 5 wt % of the alloy; when present in combination with W, Zr comprises between 0.01 and 0.5 wt % of the alloy; when present alone or in combination with Rh only, Zr comprises between 0.01 and 0.09 wt % of the alloy; and when present, Rh comprises between 0.1 and 5 wt % of the alloy. The alloys may be modified by the addition of platinum and other platinum group metals and base metals. The alloys demonstrate enhanced physical and chemical properties and are suitable for use as electrode materials in spark plugs and other high temperature applications.

1007/00//00/